



# Declaration of Performance



<b>Construction product</b>	Unitised Curtain Walling		
<b>Reference number of the Declaration of Performance</b>	90_5013_Plus_1		
<b>1. Unique identification code of the product type</b>	Hansen UniAl v.5013 Plus		
<b>2. Intended use</b>	For buildings		
<b>3. Name and address of the manufacturer</b>	HSHansen, Bredgade 4, DK-6940 Lem		
<b>5. System(s) of assessment and verification of constancy of performance</b>	3		
<b>6. Harmonised standard</b>	EN13830:2003		
<b>7. Declared performances</b>			
Reaction to fire	EN 13501-1		npd
Fire resistance	EN 13501-2 and EN 1364-4		npd
Fire propagation	EN 13501-2 and EN 1364-4		npd
Water tightness	EN 12154		RE1200
Resistance to own dead load	-		npd
Wind load resistance	EN 13116		1,6kN/6,1mm deflection
Impact resistance	EN 14019		I5 / E5
Thermal shock resistance	-		npd
Resistance to horizontal loads	-		npd
Air permeability	EN 12152		npd
Thermal resistance	EN 12631		AE1200
Airborne sound insulation	EN 410:2011	Uw (CEN size) =	0,82 W/m <sup>2</sup> K
Durability	-		npd

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer:

Date:  
10/06/2021

Signature  
CEO Simon Smidt Kristensen