



hansen

Declaration of Performance



Construction product Windows & doors

Reference number of the Declaration of Performance Nr. MB86US-SI IN 1

1. Unique identification code of the product type Hansen Vinduer Indadgående m/ skjult opluk MB86US-SI

2. Intended use Windows for buildings

3. Name and adress of the manufacturer HSHansen a/s, Randersvej 2, DK-8600 Silkeborg

4. System(s) of assessment and verification of constancy of performance 3

5. Harmonised standard EN 14351-1:2006+A2:2016

6. Declared performances

Burglary resistance ENV 1627/1628/1629/1630

Air permeability EN 1026/12207

Water tightness EN 1027/12208

Wind load EN12210

Operating forces EN 13115/12046-1

Mechanical strength EN 13115/14608/14609

Impact resistance EN 13049

Load-bearing capacity of safety devices EN 14609

Resistance to repeated opening and closing EN 12400/1191

Heat transfer coefficient EN 10077-1

Radiation Properties - Solar Factor EN 410

Radiation properties - Light transmission EN 410

Acoustic performance EN ISO 717-1

Uw (CEN size - Ug=0,53) 0,81 W/m2K

g-value = 0,56

LT-value = 0,74

npd
Class 4
Class E1350
Class C5
npd
npd
npd
npd
npd
0,81 W/m2K
0,56
0,74
npd

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

CTO Simon Smidt Kristensen

Date:
15-05-2024

Signature