Declaration of Performance





Construction product Windows & doors

Reference number of the Declaration of Performance 2310-CPR-W2789_1818_2.1_EI90_In-1

1. Unique identification code of the product type Hansen Døre MB-78 Indadgående enkelt El90

2. Intended use For buildings

4. System(s) of assessment and verification of 1 og 3

constancy of performance

EN 14351-1:2006+A2:2016; EN 16034:2014 5. Harmonised standard

6. Notified product certification body

performed the determination of the product type on the basis of type testing (including sampling), initial inspection of the manufacturing plant and of the factory production control and continuous surveillance, assessment and evaluation of factory production control and issued the certificate of 2310-CPR-W2789 performance of the product.

2310

7. Declared performances according to EN 14351-1:2006+A2:2016

Burglary resistance	ENV 1627/1628/1629/1630	
Air permeability	EN 1026/12207	
Water tightness	EN 1027/12208	
Wind load	EN12210	
Operating forces	EN 12217/12046-2	
Mechanical strength	EN 1192/947	
Impact resistance	EN 13049	
Resistance to repeated opening and closing	EN 12400/1191	
Heat transfer coefficient	EN 10077-1	Uw (CEN size - Ug=0,7)
Radiation Properties - Solar Factor	EN 410	g-value =
Radiation properties - Light transmission	EN 410	LT-value =
Acoustic performance	EN ISO 717-1	

npd
Class 4
Class 4A
Class C3/B3
Class 1
npd
Class 3
npd

Declaration of Performance





8. Declared performances according to Resistance to fire performance

EN 16034:2014

Integrity - E
Integrity and insulation EI2
Integrity and radiation - EW
Smoke Control
Ability to release
Self-closing
Durability of ability to release
Durability of self-closing against degradation

90	
90	
90	
0	
npd	
С	-
npd	
5	

9. The performance of the product idetified in points 1 and 2 is in conformity with the declared performance in point 7 and 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer:

CTO Simon Smidt Kristensen

Date:

26-08-2024

Signature

4.2-