




Declaration of Performance



Construction product

Vinduer og døre

Reference number of the Declaration of Performance

Nr. MB86N-SI IN 1

1. Unique identification code of the product type

Hansen Vinduer Indadgående MB86N-SI

2. Intended use

Windows for buildings

3. Name and address of the manufacturer

HSHansen a/s, Randersvej 2, DK-8600 Silkeborg

4. System(s) of assessment and verification of constancy of performance

3

5. Harmonised standard

EN 14351-1:2006+A2:2016

6. Declared performances

Burglary resistance

ENV 1627/1628/1629/1630

Air permeability

EN 1026/12207

Water tightness

EN 1027/12208

Wind load

EN12210

Operating forces

EN 13115/12046-1

Mechanical strength

EN 13115/14608/14609

Impact resistance

EN 13049

Load-bearing capacity of safety devices

EN 14609

Resistance to repeated opening and closing

EN 12400/1191

Heat transfer coefficient

EN 10077-1

Radiation Properties - Solar Factor

EN 410

Radiation properties - Light transmission

EN 410

Acoustic performance

EN ISO 717-1

Uw (CEN size - Ug=0,53)

g-value =

LT-value =

npd
Class 4
Class E1350
Class C5
npd
Class 4
Class 5
npd
npd
0,74-0,82 W/m2K
0,56
0,74
npd

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer:

Date:

22-08-2024

CTO Simon Smidt Kristensen

Signature